

RTL12RL FLOOR - CEILING TYPE

RTL12RL



Floor installation



Ceiling installation

RTL – RT LINE		RTL12RL
Cooling output (min – max)	Frig/h	3079
Cooling output (min – max)	W	3580
Cooling output (min – max)	BTU	12207
Heating output (min – max)	Kcal/h	3646
Heating output (min – max)	W	4240
Heating output (min – max)	BTU	14458
Humidity extraction rate	L/h	1,5
Cooling electric power (min – max)	W	1115
Heating electric power (min – max)	W	1320
EER		3,21
Energy efficiency class		A
Annual energy consumption	kWh	557,5
COP		3,21
Heating performance class		C
Power supply	V - Hz	230 – 50
N° of phases		1
Max power input cooling	W	1370
Max power input heating	W	1620
Rated cooling current	A	5,1
Rated heating current	A	6,0
Noise level I.U. max	dB(A)	41
Noise level O.U. max	dB(A)	55
I.U. air capacity (max speed)	m³/h	710
Indoor unit dimensions (WxHxD)	mm	960x660x198
Outdoor unit dimensions (WxHxD)	mm	849x540x260
Indoor unit weight	Kg	29
Outdoor unit weight	Kg	37
Type of refrigerant		R410a
Refrigerant charge	Kg	1,1
Suction pipe diameter	in	1/2
Delivery pipe diameter	in	1/4
Max refrigerating pipe lenght	m	10
Max standard charge pipe lenght	m	4
Supplementary charge pipe	g/m	20
Maximum difference in level	m	5
Type of rotary compressor		SANYO



RTLO12RL



Remote controller